




**PUBLIC UTILITY
TRANSPORTATION SYSTEMS**
LTSLSPU0098 004/03

**10 TON CAPACITY EQUIPMENT TRAILER
MODEL# A51-5527**



General:	GVWR:	24,446 lb
	GAWR:	22,224 lb
	Est. Empty Weight:	6475 lb
	Overall Dimensions:	32' 6" x 96" x 32" bed height (L x W x H)
	Deck Dimensions:	24' (19' flat 5' beaver tail) x 96" (L x W)
	Hitch:	3" Eye (adjustable 22-1/2", 27", 31-1/2" height)
	Safety Chains:	(2) 3/8" grade 70 chains with clevis hooks
Running Gear:	Axles:	(2) 12,000 lb sprung w/ oil bath hubs
	Tires:	Size: LT235/85R16 LRE
	Wheels:	6 x 16 dual steel 8 lug
	Brakes:	12-1/4" x 4" Electric (all wheels)
Frame:	Frame Rails:	Mat'l: W12 x 16 high strength steel beams
	Cross members: Mat'l:	6" junior "I" beam
Deck :	Beaver Tail:	10 degree angle
	Deck Mat'l:	Rough cut oak 2" nominal thickness
Ramps:	Dimensions:	Vertical store, spring assist 60" x 19" (L x W)
	Loading angle:	16 degrees
Finish:	Preparation:	Iron phosphate conversion treatment, chromium-free post treatment
	Primer:	Epoxy ester high solids primer
	Top Coat:	Polyurethane two component high-solids enamel
Electrical:	Wire Harness:	No Internal Splices, enclosed in protective loom
	Electrical Connection:	7-pin plug to
	Lighting:	To Federal D.O.T.
Other:	Tongue jack:	Holland/Binkley dual pin, drop leg, 20,000 lb
	Tool Box:	Mounted in tongue w/ expanded metal floor and Lockable lid - 23 1/8" front, 32 1/8" side, 37 3/4" back



MGS Incorporated