

Model # A51-8063

44,000K GVWR UTILITY TRAILER w/ TILT-BED



| | | |
|--------------------------|---|--|
| General: | GVWR: | 44,000 lbs. |
| | GAWR: | 15,000 lbs. (per axle) |
| | Empty Weight: | 9,670 lbs. (estimated) |
| | Total Capacity: | 34,000 lbs. |
| | Unladen Hitch Wt | 680 lbs. |
| | Overall Dimensions: | 424 ½" X 96" X 37 ½" (L x W x H) |
| | Deck Dimensions: | 336 ½" X 96" X 33 3/8" (L x W x H) |
| | Hitch: | 3" Towing Eye, 4 Bolt, 60,000 lbs. Gross Trailer Wgt. |
| | Safety Chains: | 13MM P7 x 37" w/ Clevis Hooks and Safety Latches |
| Running Gear: | Tires: | Size: 215/75R 17.5 Dual |
| | Wheels: | 17.5 x 6.75" with 8 bolts on a 275mm bolt circle |
| | Brakes: | Electric |
| | Axles: | 15,000 lbs. Underslung Type |
| Frame: | Frame Rails: | W14 x 26 Wide Flange Beam ASTM A572 Grade 50 |
| | Cross Members: | M6 x 4.4 Junior I Beam |
| Finish: | Preparation: | Iron phosphate conversion treatment, chromium-free post treatment |
| | Primer: | Epoxy ester high solids primer |
| | Top Coat: | Polyurethane two component high-solids enamel |
| Electrical: | Wire Harness: | No Internal Splices, enclosed in protective loom. |
| | Breakaway system: | To Federal DOT standards w/ solar maintainer |
| | Electrical Connection: | 7 way plug |
| | Lighting/Conspicuity: | Lighting To Federal D.O.T. Standards. Conspicuity tape where practicable |
| Other: | Tongue jack: | 25,000 lb. Capacity, 2 Speed Drop foot w/ Side crank |
| | Registration holder: | water tight |
| Special Features: | Aluminum Tool Box (30" x 18" x 14"), (1) Fold out Step, Aluminum Vertically stored Ramps w/ Chain Traps and Chain | |

Note: Trailer picture above may be shown with Optional Items.

MGS Incorporated

178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800-952-4228 Fax: 717-336-0514

Email: cmcquate@mgsmail.com