



PUBLIC UTILITY TRANSPORTATION SYSTEMS

LTSLSPU0134 09/05

8,000# G.V.W.R. CABLE TRAILER MODEL# A53-7000



General:	GVWR:	8,000 lb
	GAWR:	8,000 lb
	Est. Empty Weight:	1500 lb
	Overall Dimensions:	146" x 96' x 66" (L x W x H)
	Hitch:	3" eye (5 position adjustable 12-1/2" - 20-1/2" height)
	Safety Chains:	3/8" grade 43 steel chains with clevis slip hooks
	Axles:	(2) 4,000 stub spindles w/ E-Z lube
Running Gear:	Tires:	Size: 215/75R x 17.5 LRH
	Wheels:	6.75 x 17.5 steel , 8 lug
	Brakes:	12-1/4" x 3-3/8" Self-adjusting electric.
Frame:	Frame Rails:	Mat'l: 7"x3"x3/16" wall rectangular steel tube
	Cross members:	Mat'l: 7"x3"x3/16" wall rectangular steel tube and fomed 3/16" steel
Reel Carrier:	Reel size:	96" max dia. x 60" max. width x 6000 lb max wt.
	Reel shaft:	2-1/2" dia. steel
	Tensioning Brake:	16" ventilated bronze manual disc brake
Finish:	Preparation:	Iron phosphate conversion treatment, chromium free post treatment.
	Primer:	Epoxy ester high solids primer.
	Top coat:	MGS Safety Yellow - Polyurethane two component high solids enamel
Electrical:	Wire Harness:	No Internal Splices, enclosed in protective loom & routed inside frame
	Breakaway system:	12V gel cell battery Tekonsha 2010 break away switch
	Electrical Connection:	7-pin plug per SAE J560
	Lighting/Conspicuity:	Lighting To Federal D.O.T. Standards.
Other:	Tongue jack:	Hammerblow top-crank 10,000 lb lift cap.



MGS Incorporated