

Model # A53-8067 10,000K Twin Reel Multi-Use Trailer



| | | |
|--------------------------|---|--|
| General: | GVWR: | 10,000 lbs. |
| | GAWR: | 5,000 lbs. (per axle) |
| | Empty Weight: | 2800 lbs. |
| | Total Capacity: | 7200 lbs. |
| | Unladen Hitch Wt | 440 lbs. |
| | Overall Dimensions: | 226 9/16" x 85 x 69 7/16" (L x W x H) |
| | Deck Dimensions: | 159 15/16" x 59 3/4" x 23" (L x W x H) |
| | Hitch: | 3" Towing Eye, Adjustable, 60,000 Lbs. Gross Trailer Wgt. |
| | Safety Chains | 3/8" System 4 w/ 3/8" Clevis Hooks and Safety Latches |
| Running Gear: | Tires: | Size: ST 225/75R 15 LRD (Dual) |
| | Wheels: | 15 x 6" with 6 bolts on a 5.5" bolt circle, Steel |
| | Brakes: | Electric |
| | Axles: | 5000 lbs. Dexter Spring Type |
| Frame: | Frame Rails: | C8 x 11.5 Structural Channel ASTM A36 |
| | Cross Members: | 7 Gauge HR Sheet ASTM A569 |
| Finish: | Preparation: | Iron phosphate conversion treatment, chromium-free post treatment |
| | Primer: | Epoxy ester high solids primer |
| | Top Coat: | Polyurethane two component high-solids enamel |
| Electrical: | Wire Harness: | No Internal Splices, enclosed in protective loom. |
| | Breakaway system: | To Federal DOT standards w/ solar maintainer |
| | Electrical Connection: | 6 way plug |
| | Lighting/Conspicuity: | Lighting To Federal D.O.T. Standards. Conspicuity tape where practicable |
| Other: | Tongue jack: | 7000 lb. Capacity, Drop foot, Top wind, Center mounted |
| | Registration holder: | water tight |
| Special Features: | (2) Spindle Bar Frames and (2) Spindle Bars, Tailgate | |
| Options: | 16" ventilated silicon-bronze manual disc brake(requires upgrade to reel bar with power arm and a 3-4" reduction in usable reel bar width. Bussbar, ground kit, Reel coupling rackets/storage bracket, Reel bar storage brackets (both sides), Tool Box | |

MGS Incorporated

178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800-952-4228 Fax: 717-336-0514

Email:cmcquate@mgsmail.com