

Model #ECF20025 15.8K FIXED TRIPLE REEL TRAILER



General:	GVWR:	22,000 lbs.
	GAWR:	10,000 lbs. (per axle)
	Empty Weight:	6,200 lbs.
	Total Capacity:	15,800 lbs.
	Overall Dimensions:	291 3/16" x 96" x 76 1/4" (L x W x H)
	Deck Dimensions:	210 3/16" x 96" x 76 1/4" (L x W x H)
	Hitch:	3" towing eye, adjustable 60,000 Lb. rating
	Safety Chains:	1/2" Grade 70 to 49" long Clevis Slip Hook w/ Latch
Running Gear:	Tires:	Size: LT235/85R/6LRE Dual 3000#@80psi
	Wheels:	16x6" with bolts on a " bolt circle"
	Brakes:	Electric
	Axles:	10,000 lbs. Dexter Spring Type
Frame:	Frame Rails:	W10 x 26 wide flange beam ASTM A36
	Cross Members:	4" x 2" x 3/16" wall Structural steel tubing
Reel Carriers:	Reel Size:	72" max. Diameter x 52" max. width x 4000 lbs. max. wgt.
	Reel Shaft:	(3) 2 1/2" diameter
Finish:	Preparation:	Iron phosphate conversion treatment, chromium-free post treatment
	Primer:	Epoxy ester high solids primer
	Top Coat:	Polyurethane two component high-solids enamel
Electrical:	Wire Harness:	No Internal Splices, enclosed in protective loom.
	Breakaway system:	To Federal DOT standards w/ solar maintainer
	Electrical Connection:	(7) prong pin plug
Other:	Lighting/Conspicuity:	Lighting To Federal D.O.T. Standards. Conspicuity tape where practicable
	Tongue jack:	10,000lb. Capacity, top wind
	Registration holder:	water tight
Special Features:	(5) Fold out Steps, (3) Tensioning Brakes w/ 16" Bronze Ventilated Disk, (2) 10K Stabilizer Jacks, 3" galvanized Spindle Bars, Suitable for Overhead or Underground, Optional Retrievers on all reels	