

**TWIN REEL SINGLE TURRET MODEL# ECT20000**



<b>General:</b>	GVWR:	6,600 lb
	GAWR:	6,000 lb
	Est. Empty Weight:	2,840 lb
	Overall Dimensions:	180.5" x 99' x 78" (L x W x H)
	Hitch:	3" eye (adjustable 28" bottom of eye in center position)
	Safety Chains:	3/8" grade 43 steel chains with clevis slip hooks
	Axle:	6,000# w/ E-Z lube
<b>Running Gear:</b>	Tires:	Size: 235/80R x 16 LRE
	Wheels:	6 x 16 steel , 8 lug on 6.75 center
	Brakes:	12" electric.
<b>Frame:</b>	Frame Rails:	C8 x 11.5 Structural Channel
	Cross members:	7ga steel
<b>Reel Carrier:</b>	Dimensions:	2-1/2"dia. hot dipped galvanized steel tube standard
<b>Finish:</b>	Preparation:	Iron phosphate conversion treatment, chromium free post treatment.
	Primer:	Epoxy ester high solids primer.
	Top coat:	MGS Safety Yellow - Polyurethane two component high solids enamel
<b>Electrical:</b>	Wire Harness:	No Internal Splices, enclosed in protective loom & routed inside frame
	Breakaway system:	12V gel cell battery Tekonsha 2010 break away switch
	Electrical Connection:	7-pin plug per SAE J560
	Lighting/Conspicuity:	Lighting To Federal D.O.T. Standards.
<b>Other:</b>	Tongue jack:	Hammerblow top-crank 10,000 lb lift cap.
	Reel lock with integral tapered bushing included	

**MGS Incorporated**