

ECT20009 TRIPLE TURRET



General:	GVWR:	26,400 lbs.
	GAWR:	12,000 lbs. (per axle)
	Empty Weight:	10,150 lbs.
	Total Capacity:	16,250 lbs.
	Turret Capacity:	8,000 lbs. / Turret
	Overall Dimensions:	29' x 8' x 7' (L x W x H)
	Deck Dimensions:	21'9" x 5'-7" x 27 3/4" (L x W x H)
	Hitch:	3" towing eye, adjustable 60,000# rating
	Safety Chains:	1/2" steel chains with clevis slip hooks
Running Gear:	Tires:	Size: 235/85R16 Dual 3,000# Cap/Tire, 110# PSI
	Wheels:	16" with 8 bolts on a 6.5" bolt circle
	Brakes:	Air Brakes with Haldex ABS (2S1M) to DOT specifications Spring brakes and auto slack adjusters
Frame:	Axles:	(2) 12,000 lbs. Dexter HD Spring Type
	Frame Rails:	Mat'l: 8" x 4" x 1/4 A500B
	Cross Members:	Mat'l: 8" x 4" x 1/4 A500B
Reel Carrier:	Turret:	(3) Turrets on 36" greasable turntable bearings lockable on 22.5 deg.
	Usable Spindle Width:	66"
	Max Reel Diameter:	64"
	Reel shaft:	(3) 2-1/2" dia. with integral power arm, tapered collar and lift point
	Locking Collar:	(3) galvanized with integral tapered collar and lift point
Deck :	Material:	3/16" steel deck plate ASTM A786
Access:	Steps:	Running boards in front and behind fenders with (2) fold out steps and folding handrails per side (non skid treatment applied to entire deck)
Finish:		Hot dipped galvanizing
Electrical:	Wire Harness:	No Internal Splices, enclosed in protective loom.
	Breakaway system:	To Federal DOT standards
	Electrical Connection:	7pin plug
	Lighting/Conspicuity:	Lighting To Federal D.O.T. Standards. Conspicuity tape where practicable
Other:	Tongue jack:	10,000 lb. Capacity, Topwind
	Stabilizer jacks:	(2) adjustable drop leg. Rear Mounted
	Registration holder:	water tight
Optional Items:		16" ventilated silicon-bronze manual disc brake, Bussbar, ground kit

MGS Incorporated