

Model #EEE20028 16' Hotstick Trailer



Trailer may be shown with optional equipment

General:	GVWR:	10,000lbs
	Rated Payload	6,000lbs
	Est. Empty Weight:	4,000lbs
	Overall Dimensions:	20' x 8' x 8.5' (L x W x H)
	Tongue Jack:	yes
	Hitch:	3" Pintle Eye, adjustable
	Safety Chains:	3/8" x 40" grade 40, w/ clevis hook and safety latch
Running Gear:	Axles:	(2)-5000lb torsion axles
	Brakes:	Electric (all wheels)
	Tires:	Size:LT215/85R16 Ply: Load Range D
	Wheels:	Rim: Silver spoke steel Bolt circle: 8 lugs on 6.5" center
Frame Structural:	Frame:	Mat'l: Steel tube main rails with formed steel cross members
Finish:	Exterior:	0.30 aluminum skin (pre painted).
Interior:	Walls:	1/4" plywood with vinyl coating
	Floor/Ramp gate:	Rhino Lining
Lighting & Reflectors:	To meet D.O.T. specifications. All lights are sealed Trucklite or equivalent	
Wire Harness:	Continuous, no splices	
Electrical Connection:	6-pin min.	
Special Features:	Flush floor (no wheel boxes), Interior step at side door, Exterior fold out step at side door, Low storage bins both sides (galvanized), Vertical and horizontal tie off racks on front wall, aluminum hook rack on front wall, Low storage bins on front wall (galvanized), Hot stick racks w/ adjustable pins on side walls and center of trailer, 1500W heater, Four drawer storage unit, Four 12V LED interior lights. 12V battery to power interior lights mounted under floor. Battery is wired to 40A panel	

