

Model # EFT20001 Oil Filter Trailer

(Filtration Objective – Removal of Particulate, Carbon, and Water to Restore Dielectric and Insulating Value)



General:	GVWR:	5700 lbs.
	GAWR:	5200 lbs. (per axle)
	Empty Weight:	2140 lbs.
	Total Capacity:	3060 lbs.
	Unladen Hitch Wt	240 lbs.
	Overall Dimensions:	151 3/16" x 74 1/2" x 55 11/16" (L x W x H)
	Deck Dimensions:	88" x 52" x 35 1/4" (L x W x H)
	Hitch:	3" Towing Eye, 4 Bolt, 60,000 lbs. Gross Trailer Wgt.
	Safety Chains:	5/16" Safety Chain x 42" w/ 3/8" Clevis Hooks and Safety Latches
Running Gear:	Tires:	Size: ST 225/75R 15 LRD
	Wheels:	15 x 6" with 6 bolts on a 5.5" bolt circle, Steel
	Brakes:	Electric
	Axles:	5200 lbs. Dexter Spring Type
Frame:	Frame Rails:	C4 x 5.4 Structural Steel Channel ASTM A36
	Cross Members:	7 Gauge HR Sheet ASTM A569
Finish:	Preparation:	Iron phosphate conversion treatment, chromium-free post treatment
	Primer:	Epoxy ester high solids primer
	Top Coat:	Polyurethane two component high-solids enamel
Electrical:	Wire Harness:	No Internal Splices, enclosed in protective loom.
	Breakaway system:	To Federal DOT standards w/ solar maintainer
	Electrical Connection:	7 way plug
	Lighting/Conspicuity:	Lighting To Federal D.O.T. Standards. Conspicuity tape where practicable
Other:	Tongue jack:	5000 lb. Capacity, Sidewind
	Registration holder:	water tight
Special Features:	(1) Hanney Hose Reel #N818-25-26B w/ 3/4" x 50' of Hose, (1) Ertel-Alsop "Disk Pak" Oil Filter, (2) Stainless Steel Tanks, (1) Blackmer Power Pump #XFIC (1 H.P. @ 1750 rpm), (6) Selection Valves, Drain, Enclosed Compartment	

MGS Incorporated