

Model # EMU20026 Multi-Use Trailer



General:	GVWR:	10,000 lbs.
	GAWR:	10,000 lbs. (per axle)
	Empty Weight:	3200 lbs.
	Total Capacity:	6800 lbs.
	Unladen Hitch Wt	140 lbs.
	Overall Dimensions:	177 1/8" x 92" x 40 3/8" (L x W x H)
	Deck Dimensions:	108 5/8" x 86" x 12" (L x W x H)
	Hitch:	3" Towing Eye, 4 Bolt, 60,000 Lbs. Gross Trailer Wgt.
	Safety Chains:	3/8" Grade 70 w/ 1/2" Clevis Hooks and Safety Latches
Running Gear:	Tires:	Size:245/70R 17.5 LRH
	Wheels:	17.5 x 6.5" with 8 bolts on a 6.5" bolt circle, Steel
	Brakes:	Air – ABS Equipped, 2 SIM, Spring Brake Release
	Axles:	10,000 lbs.
Frame:	Frame Rails:	5 x 3 x 3/16" Wall Steel Tube ASTM A500B
	Cross Members:	5 x 3 x 3/16" Wall Steel Tube ASTM A500B
Finish:	Preparation:	Iron phosphate conversion treatment, chromium-free post treatment
	Primer:	Epoxy ester high solids primer
	Top Coat:	Polyurethane two component high-solids enamel
Electrical:	Wire Harness:	No Internal Splices, enclosed in protective loom.
	Electrical Connection:	7 way plug
	Lighting/Conspicuity:	Lighting To Federal D.O.T. Standards. Conspicuity tape where practicable
Other:	Tongue jack:	7000 lb. Capacity, Pivoting, Top wind
	Registration holder:	water tight
Special Features:	(2) Pole Cable Winches that allow for 360 degree Pole wrap, Pole chocks, Pole skid Storage Box, Tailgate	
Options:	#ECF20027 Reel Frame 16" Ventilated Bronze Manual Tensioning Brake	

Note: Trailer picture above may be shown with Optional Items.



MGS Incorporated

178 Muddy Creek Church Rd. Denver, PA 17517 Phone: 800-952-4228 Fax: 717-336-0514
Email:cmcquate@mqsmail.com