



**PUBLIC UTILITY
TRANSPORTATION SYSTEMS**

**MODEL # EPT20018 GALVANIZED POLE TRAILER
8000LB. CAPACITY**

LTSLSPU0141 7/16/08



GVWR	10,500 LB
EMPTY WEIGHT	2,250 LB
CAPACITY	8,250 LB
DIMENSIONS	108"L X 79"W X 36 1/2" LOADED HEIGHT
GENERAL CONSTRUCTION	4" X 6" X 1/4" STRUCTURAL TUBE FRONT TO REAR 4" X 6" X 1/4" STRUCTURAL TUBE FRAME RAILS
POLE SECUREMENT	TWO FULL WIDTH POLE BUNKS WITH CENTERING GUIDES. TWO SLIDING ADJUSTABLE BOLSTERS WITH STOP BOLT PER BUNK. BINDER HUBS ON POLE BUNK FOR 180° LEAD POLE WRAP
FRONT JACK	7,000LB STATIC LOAD SIDE WIND TRUNNION MOUND JACK BOLT RETAINED W/ 4" X 6" SANDSHOE.
AXLE	10,000LB HD SPRUNG AXLE, 12.25" X 4" FORWARD SELF ADJUSTING ELECTRIC BRAKES
TIRE & WHEEL	215/75R 17.5LRH 17.5 X 8.25
COUPLER	TOWING EYE, 3" 60,000 LB. CAP. BOLT ON
SAFETY CHAINS	3/8" GRADE 70 W/ 1/2" SPRING CATCH HOOK
BINDERS	(3) 6000 LB RATCHET WINCH W/ SAFETY RELEASE (3) 4" X 27' POLYESTER LATEX WINCH STRAPS W/ DELTA RING
FINISH	HOT DIPPED GALVANIZING WITH NON SKID COATING ON FENDERS
ELECTRICAL	TRUCK-LITE SHOCK MOUNTED LED LIGHTS & SEALED WIRING HARNESSES THROUGHOUT, SEALED AND TERMINATED INTO JUNCTION BOXES, FRONT PLUG SOCKET, SEALED BREAKAWAY SWITCH WIRED TO SOLAR MAINTAINED BATTERY
LIGHT BAR	INTEGRAL YELLOW POWDER COAT ALUMINUM W/ LED LIGHTS. 25 FOOT INTEGRAL CORD TWO SPRIN BIND FLAG HOLDERS
POLE DRAWBAR	12,500 LB CAP. W/ 3" EYE & 3/8" G8 SAFETY CHAINS (BOLTS TO POLE) HOT DIP GALVANIZED STORES ON TRAILER



MGS Incorporated

178 Muddy Creek Church Rd. Denver, PA 17517 Phone: 800-952-4228 Fax: 717-336-0514

Email: cmcquate@mgsmail.com