

## Model #EPT20032 10K Telescopic Pole Trailer w/ 7K Capacity



<b>General:</b>	GVWR:	10,000 lbs.
	GAWR:	10,000 lbs. (per axle)
	Empty Weight:	2,900 lbs.
	Total Capacity:	7,000 lbs.
	Unladen Hitch Wt	280 lbs. w/ Tongue Retracted and Level
	Overall Dimensions:	248 15/16" x 90" x 56 3/8" (L x W x H) Length @ Full Extension – 356 13/16"
	Deck Dimensions:	117" x 90" x 28 3/8" (L x W x H)
	Hitch:	3" Eye Bolt, 4 Bolt, 60,000 Gross Trailer Wgt.
	Safety Chains:	½" Grade 70 (54" Long) w/ Clevis Slip Hooks and Safety Latches
<b>Running Gear:</b>	Tires:	Size: 235/75R 17.5 LRH
	Wheels:	17.5" with 8 bolts on a 6.5" bolt circle
	Brakes:	Electric
	Axles:	10,000lbs. Heavy Duty Underslung Type
<b>Frame:</b>	Frame Rails:	8 x 4 x ¼" Wall Tube ASTM A500B
	Cross Members:	¼" H. R. Plate ASTM A36
<b>Finish:</b>	<i>Hot dipped galvanizing</i> or	
	Preparation:	Iron phosphate conversion treatment, chromium-free post treatment
	Primer:	Epoxy ester high solids primer
	Top Coat:	Polyurethane two component high-solids enamel
<b>Electrical:</b>	Wire Harness:	No Internal Splices, enclosed in protective loom.
	Breakaway system:	To Federal DOT standards w/ solar maintainer
	Electrical Connection:	7 way pin plug
	Lighting/Conspicuity:	Lighting To Federal D.O.T. Standards. Conspicuity tape where practicable
<b>Other:</b>	Tongue jack:	(2) 7,000 lb. Capacity, Sidewind/ Fixed Leg
	Registration holder:	water tight
<b>Special Features:</b>	Winch Bar, (3) Ratcheting Pole Winches, Integrated Light Bar w/ (2) Day-Glo Flags, Aluminum Diamond Plate Tool Box (22x10x10)	