

Model # GCP10005
Galvanized Horizontal Coil Trailer
 (Available in Painted Finish as Model # A56-5605B)



- General:** GVWR: 3,000 lbs.
 GAWR: 3,500 lbs. (per axle)
 Empty Weight: 1,580 lbs. (galvanized) 1400 lbs. (painted)
 Unladen Hitch Wt: 200 lbs.
 Overall Dimensions: 157 3/4" x 98 7/8" x 82" (L x W x H)
 Hitch: 3" Towing Eye, 2 Bolt
 Safety Chains: 3/8" System 4 w/ 3/8" Clevis Hooks and Safety Latches
- Running Gear:** Tires: Size: ST 205/75R 15 LRC
 Wheels: 15 x 5" JJ, Steel (white) with 5 bolts on a 4.5" bolt circle
 Brakes: Electric
 Axles: 3500lbs. Dexter Model 10 "Torflex" Type
- Frame:** Frame Rails: C5 x 6.7 Structural Channel ASTM A36
 Cross Members: 1/4" H.R. Plate ASTM A36
- Finish:** *Hot dipped galvanizing or painted*
- Carousel:** Turntable Data: (1) adjustable turntable incorporating removable vertical I.D. posts located by spring pins with greasable roller bearing spindle. O.D. posts adjustable for two and three inch pipe. Manually actuated turntable brake
 Carousel Dimensions: 97 1/2" between or 101 1/2" between O.D. posts.
 I.D. posts adjustable from 32" - 66" (outside of post dimension)
 Post Height (from carousel) 48"
- Electrical:** Wire Harness: No Internal Splices, enclosed in protective loom.
 Breakaway system: To Federal DOT standards w/ solar maintainer
 Electrical Connection: 7 way plug
 Lighting/Conspicuity: Lighting To Federal D.O.T. Standards. Conspicuity tape where practicable
- Other:** Tongue jack: 7000 lb. Capacity, Drop foot, Top wind
 Registration holder: watertight
- Special Features:** Tracer Wire Holder
- Options:** Self-Load Kit

Note: Trailer pictures above may be shown with Optional Items.