

**TILTING COIL TRAILER  
MODEL# GCT10000**



<b>General:</b>	GVWR: 3,750 lb..
	GAWR: 3,500 lb.
	Est. Empty Weight: 1,700 lb.
	Overall Dimensions: 153 1/2" x 96" x 83 3/4" (L x W x H) empty
	Hitch: 3" Lunette Eye (adjustable)
	Safety Chains: (2) 5/16" grade 40 chains with clevis slip hooks
	Tongue jack: 7,000 drop foot, top wind
<b>Running Gear:</b>	Axles: (1) 3,500 lb. Dexter "torflex" torsion axle
	Tires: Size: ST205/75 R15 LRC
	Wheels: 15 x 5 steel 5 lug on 4 1/2" centers
	Brakes: Electric with D.O.T. compliant breakaway system
<b>Frame:</b>	Frame Rails: Mat'l: W5 x 6.7 Structural channel Grade: ASTM A36
<b>Finish:</b>	Preparation: Iron phosphate conversion treatment, chromium-free post treatment
	Primer: Epoxy ester high solids primer
	Top Coat: Polyurethane two component high-solids enamel
<b>Lighting:</b>	Wire Harness: No Internal Splices, enclosed in protective loom
	Electrical Connection: 6-pin plug min. required
	Lighting: To Federal D.O.T.
<b>Turntable Data:</b>	(1) adjustable turntable incorporating removable vertical I.D. and O.D. posts located by spring pins with greasable roller bearing spindle.
	Manually actuated turntable brake.
	Removable O.D. posts, adjustable O.D.'s of 97 1/2" and 101 1/2"
	Carousel Dimensions:
	I.D. posts adjustable from 32" - 66" (outside of post dimension)
	Post Height (from carousel) 48"
<b>Tilt:</b>	Hydraulic hand pump standard - Approximately 70 pumps to raise or lower carousel.
	Carousel raises to 90 degrees
	Drop down rear stabilizers standard
<b>Options:</b>	Tracer wire kit, Wheel chock holders, Electric or engine driven HPU available



**MGS Incorporated**

178 Muddy Creek Church Rd. Denver, PA 17517 Phone: 800-952-4228 Fax: 717-336-0514

Email: cmcquate@mgsmail.com