

Model # UOP30005 Material Hauler



General:	<p>GVWR: 15,400 lbs. GAWR: 7000 lbs. (per axle) Empty Weight: 4,260 lbs. Total Capacity: 11,100 lbs. Unladen Hitch Wt: 500 lbs. Overall Dimensions: 246 5/8" x 102" x 48 7/8" (L x W x H) Deck Dimensions: 168" x 74 3/4" x 24 (L x W x H) Hitch: 3' Towing Eye, 4 Bolt, 60,000 Lbs. Gross trailer Wgt. Safety Chains: 3/8" Grade 70 w/ 3/8" Clevis Hooks and Safety Latches</p>
Running Gear:	<p>Tires: Size: LT235/85R16 LRG Wheels: 16 x 6" with 8 bolts on a 6.5" bolt circle, Conventional Steel Brakes: Electric Axles: 7000 lbs. Underslung Type</p>
Frame:	<p>Frame Rails: 6 x 4 x 1/4" Wall Rectangular Tube ASTM A500B Cross Members: 2 x 2 x 2 x 3/16" Structural Steel Tube ASTM A500</p>
Finish:	<p><i>Hot dipped galvanizing</i></p>
Electrical:	<p>Wire Harness: No Internal Splices, enclosed in protective loom. Breakaway system: To Federal DOT standards w/ solar maintainer</p>
Other:	<p>Electrical Connection: 7 way plug Lighting/Conspicuity: Lighting To Federal D.O.T. Standards. Conspicuity tape where practicable Tongue jack: 7000 lb. Capacity, Drop foot and Side wind Registration holder: water tight</p>
Special Features: Tool Box (45" x 18" x 24") .125 Diamond Bright Aluminum w/ Paddle Latch, Gas Springs, and Neoprene Weather Seal	
Note: Trailer picture above may be shown with Optional Items.	

MGS Incorporated