



**PUBLIC UTILITY
TRANSPORTATION SYSTEMS**

LTSLSPU0073 04/03

**CABLE REEL TRANSPORT THREE SPINDLE
MODEL# A53-3611**



General:	GVWR:	5500#
	Rated Payload	3760#
	Est. Empty Weight:	1740#
	Overall Dimensions:	154 7/32" x 76 1/8" x 47" (L x W x H) empty
	Deck Dimensions:	102" x 50" x 22 3/4" (L x W x H)
	Tongue Jack:	7000# top wind
	Hitch:	3" Pintle Eye, adjustable
	Safety Chains:	3/8" x 40" grade 70, w/ clevis hook and safety latch
Running Gear:	Axles:	5000# Dexter torsion
	Brakes:	Electric 12" x 2"
Tires:	Size:225/75R 15	Load Range D
	Wheels:	Rim: 15" x 6" steel Bolt circle: 6 on 5.5
Finish:	Prep:	Iron phosphate conversion treatment, chromium free post tmt.
	Primer:	Epoxy ester high solids primer
	Top Coat:	Polyurethane two component high solids enamel
Lighting & Reflectors:	To meet D.O.T. specifications.	
Wire Harness:	Continuous, no splices	
Electrical Connection:	6-Prong receptacle min	
Reel Data:	Max Width: 41 1/2"	
	Dist. between reel centers: 28"	



Hot dipped galvanized finish also available