



PUBLIC UTILITY TRANSPORTATION SYSTEMS

LTSLSPU0078 04/03

16' HOTSTICK TRAILER W/ADDED GROUND CLEARANCE MODEL# A53-5186



General:	GVWR:	10,000lbs
	Rated Payload	6,000lbs
	Est. Empty Weight:	4,000lbs
	Overall Dimensions:	20' x 8' x 8.5' (L x W x H)
	Tongue Jack:	yes
	Hitch:	3" Pintle Eye, adjustable
Running Gear:	Safety Chains:	3/8" x 40" grade 40, w/ clevis hook and safety latch
	Axles:	(2)-5000lb torsion axles
	Brakes:	Electric (all wheels)
	Tires:	Size:LT215/85R16 Ply: Load Range D
Frame Structural:	Wheels:	Rim:Silver spoke steel Bolt circle: 8 lugs on 6.5" center
	Frame:	Mat'l: Steel tube main rails with formed steel cross members
Finish:	Exterior:	0.30 aluminum skin (pre painted).
Interior:	Walls:	1/4" plywood with vinyl coating Floor: 3/4" plywood (painted)

Lighting &

Reflectors: To meet D.O.T. specifications. All lights are sealed Trucklite or equivalent

Wire Harness: Continuous, no splices

Electrical Connection: 6-pin min.

Special features: Flush floor (no wheel boxes), Interior step at side door, Exterior fold out step at side door, Low storage bins both sides (galvanized), Vertical and horizontal tie off racks on front wall, Aluminum hook rack on front wall, Low storage bins on front wall (galvanized), Hot stick racks w/ adjustable pins on side walls and center of trailer, 1500W heater, Four drawer storage unit, Two pullout ramps at rear of trailer and Four 12V fluorescent lights.



MGS Incorporated

178 Muddy Creek Church Rd. Denver, PA 17517 Phone: 800-952-4228 Fax: 717-336-0514

Email cmcquate@mgsmail.com