

HOT STICK TRAILER MODEL#A53-5039



General:	GVWR:	7,700lbs
	Rated Payload	4,200lbs
	Est. Empty Weight:	3,500lbs
	Overall Dimensions:	21' x 8' x 8.5' (L x W x H)
	Tongue Jack:	yes
	Hitch:	3" Pintle Eye, adjustable
Running Gear:	Safety Chains:	3/8" x 40" grade 40, w/ clevis hook and safety latch
	Axles:	(2)-3500lb torsion axles
	Brakes:	Electric (all wheels)
	Tires:	Size:LT205/75R15 Ply: Load Range C
Frame Structural:	Wheels:	Rim:solid steel Bolt circle: 5 lugs on 4.5" center
	Frame:	Mat'l: Steel tube main rails with formed steel cross members
	Exterior:	0.30 aluminum skin
Finish:		Roller coated aluminum (choice of several colors)
Interior:	Walls:	1/4" plywood with vinyl coating
	Floor:	3/4" plywood (painted)
Lighting & Reflectors:		To meet D.O.T. specifications. LED tail lights, All lights are sealed Trucklite or equivalent.
Wire Harness:		Continuous, no splices
Electrical Connection:		6-Pin min
Special features:		Exterior fold out step at side door, Low storage bins both sides (galvanized), Vertical and horizontal tie off racks on front wall, Low storage bins on front wall (galvanized), Hot stick racks,w/adjustable pins on side walls and center of trailer, 1500W heater, Four drawer storage unit and four 12V fluorescent lights.

