



PUBLIC UTILITY TRANSPORTATION SYSTEMS

LTSLSPU0090 04/03

48' TOOL TRAILER MODEL# A51-5607



General:	GVWR:	20,000#
	Rated Payload	12,000#
	Est. Empty Weight:	8,000#
	Est. Overall Dimensions:	40' x 102" x 134" (L x W x H)
	Jacks:	(2)-10,000# two speed stiff legs (front), (2)- adjustable drop legs (rear)
	Hitch:	King Pin
Running Gear:	Axles:	8,000# Dexter torsion axle
	Brakes:	Electric
	Tires:	Size: 215/75R 17.5 Ply: Load Range H Type: High speed Trailer
	Wheels:	Rim: 17.5x7.50 Dex. (solid) Bolt circle: 8 on 6.5" center
Frame Structural:	Frame: Mat'l:	3 x 8 x 3/16 Structural Tube Fully Undercoated
	Cross Members:	12ga Formed channels Fully Undercoated
Exterior:		.040 Aluminum Roller coated skin w/ vertical supports on 16" centers
Lighting & Reflectors:		To meet DOT Specifications Separate Brake and Turn Signals
Wire Harness:		Continuous 5/16" Diam. Protective Loom
Electrical Connection:		6-Prong receptacle Minimum required

Features:

MGS Incorporated

178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800-952-4228 Fax: 717-336-4071

Email: cmcquate@mgsmail.com