



PUBLIC UTILITY TRANSPORTATION SYSTEMS

LTSLSPU0100 04/03

SELF-LOADING CABLE REEL TRAILER MODEL# A53-5052



General:	GVWR:	3,000 lb	
	Rated Payload:	2,000 lb	
	Est. Empty Weight:	1,000 lb	
	Overall Dimensions:	114" x 96" x 54" (L x W x H)	
	Tongue Jack:	7,000 lb Capacity, Drop leg, Topwind w/ Dolly wheel	
	Hitch:	3" Pintle Eye, adjustable	
	Safety Chains:	5/16" Blue chrome grade 40, w/ clevis hook and safety latch	
Running Gear:	Axles:	3,500 lb Torflex suspension	
	Brakes:	NA	
	Tires:	Size: ST205/75R15 LRC	
	Wheels:	Rim: 15 x 6 Bolt circle: 5 on 4 1/2	
Frame Structural:	Frame Rails:	Mat'l: C5 x 6.7# Structural channel	Grade: ASTM A36
	Cross members:	Mat'l: 2 x 2 x 3/16 Structural tubing	Grade: ASTM A569
Finish:	Paint:	Preparation: Iron phosphate conversion treatment, chromium-free post treatment Primer: Epoxy ester high solids primer Top Coat: Polyurethane two component high-solids enamel	
Lighting & Reflectors:		To Federal DOT Requirements	
	Wire Harness:	Continuous 5/16" Diam. Protective Loom	
	Electrical Connection:	4 post min.	
Miscellaneous:	(2) Independent reel carriers, electric self load		
	Reel Size:	(2) 58" x 30"	
	Electric Winch:	(2) 1500 # Line pull capacity	



MGS Incorporated

178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800-952-4228 Fax: 717-336-0514

Email: cmcquate@mgsmail.com